BEST AVAILABLE COPY

Phase Diagrams for Ceramists Volume VI

General Editors

Robert S. Roth, NBS

Jennifer R. Dennis, ACerS/NBS

Howard F. McMurdie, ACerS Consultant

Editorial Associates, National Bureau of Standards

Mary A. Clevinger Helen M. Ondik

Graphics Programmer, National Bureau of Standards
Peter K. Schenck

Compiled at the Ceramics Division, National Bureau of Standards

The American Ceramic Society

757 Brooksedge Plaza Drive, Westerville, Ohio 43081-2821

BEST AVAILABLE COPY





NSRDS

The National Standard Reference Data System comprises a set of data centers and other data evaluation projects coordinated by the Office of Standard Reference Data of the National Bureau of Standards. The aim of this program is to provide reliable reference data on physical and chemical properties to the scientific and technical community of the United States. Evaluated data produced under the program are published in the Journal of Physical and Chemical Reference Data, a joint publication of the American Institute of Physics, the American Chemical Society, and the National Bureau of Standards, as well as other appropriate media.

The Phase Diagrams published in this volume were collected and reviewed by the Phase Diagrams for Ceramists Data Center, located in the National Measurement Laboratory of the National Bureau of Standards. We are pleased that this cooperative effort between the American Ceramic Society and the National Bureau of Standards continues to provide important reference information to the ceramics community.

David R. Lide, Jr., Chief Office of Standard Reference Data National Bureau of Standards

Copyright 1981

The American Ceramic Society

All Rights Reserved

Figs. 1404-6465

Dy₂O₃-ZrO₂ (concl.)






Fig. 6464—System Dy₂O₃-ZrO₂. (A) Zirconia-rich region of the tentative zirconia-dysprosia system; (B) effect of dysprosia on tetragonal-monoclinic transformation temperature of zirconia on cooling; (C) phase diagram for zirconia-dysprosia system. M, Mon = monoclinic; F = cubic fluorite-type; T, Tet = tetragonal; C = cubic rare earth oxide-type; $H_2 = M_7O_{11.5}$ -type; $H_3 = M_7O_{11}$ -type; H = hexagonal high temperature rare earth oxide-type; B = monoclinic rare earth oxide-type.

C. Pascual and P. Duran, J. Mater. Sci., 15 [7] 1701-1708 (1980).

Zirconia (99.8%) and dysprosia (99.9%) were mixed by grinding, pressed, and sintered at 1300°C. They were then refired at 1800°C or melted in a solar furnace, reground, pressed into pellets, and heated to 1765°C in air, using wire wound furnaces in air or gas firing. A few firings above 2000°C were in flowing Ar-5% H2. Compositions were investigated at 5% intervals and were contained in Pt foil below 1250°C.

Temperatures were controlled by thermocouples to 1750°C, and by optical pyrometer at higher temperatures. Quenched specimens were analyzed by X-ray diffraction. High temperature X-ray diffraction, to 1500°C in air, was used to analyze specimens containing 0 to

The diagrams are in essential agreement with the closely related ZrO2-rare earth systems. See Figs. 2363 and 5211 for somewhat differing results. The depression of the ZrO2 transformation is as expected. D.R.W.

$Dy_2O_3-V_2O_5$




Fig. 6465-System V2O5-DyVO4. G. A. Rykova, O. N. Ustalova, V. M. Skorikov, and I. V. Tananaev, Zh. Neorg. Khim., 24 [1] 183-187 (1979); Russ. J. Inorg. Chem. (Engl. Transl.), 24 [1] 102-105 (1979).

Experimental details are the same as those described in the commentary accompanying Fig. 6476. The orthovanadate compound, DyVO4, was found to melt congruently. The presence of V(IV) in these compounds could not be detected by magnetic susceptibility measurements. The enthalpy of formation (670°C) of the orthovanadate was determined to ±3% from DTA traces, using CaCO, as a calibration standard.

DyVO4 is tetragonal and of the ZrSiO4 type. See Fig. 2364 for the polymorphism of DyVO4 under pressure.

M.F.B.

BEST AVAILABLE COPY

THIS PAGE BLANK (USPTO)